HAND DRY CUTTER 8203 THE COMPACT

Metal cutting circular saw by Jepson Power for fast and burr-free sawing of metal pipes and profiles without coolin

Ideal for sawing steel, sheet steel, sandwich panels, metal plates, pipes and profiles made of steel, non-ferrous materials and composites (optionally with impact-resistant LBS saw blade)

- Equipped as standard with a resharpenable Ø 203 / 42T carbide tipped saw blade for steel and stainless steel
- · Solid and light: only 6.3 kg
- · Chip collecting container for clean work
- · Lubricant unnecessary
- Max. cutting depth of 67/42 mm bevel cut, up to a thickness of 10 mm
- · Set of 2 adapters for guide rail

CHIP COLLECTOR





Ideal for cutting metal grids with LBS saw blade, impactresistant Ref.: 608295LBS

Hand Dry Cutter 8203 230V



Optional: Guide rail 1.400 mm with 2 C-clamps and adapter 608275SET



Depth adjustment with scaling



Chip collector



45° bevel cut

Power input	Voltage	No load speed	Net weight	Blade size	Bore	Cable length
1.700 W	230V / 50Hz	3.700 min ⁻¹	6,3 kg	Ø 203 mm	Ø 25,4/20	5 m

Reference

608275B

with 203 / 42T for steel + stainless steel (Inox)	608295
with 203 / 48T LBS saw blade impact-resistant	608295LBS
with 203 / 42T for steel + stainless steel (Inox) with guide rail set 1.400 mm incl. 2 quick release clamps and adapter for guide rail 1.400 mm	
Saw blades	Reference
203 / 42T for steel + stainless steel	721203421
200 / 48T for aluminum	72120048A
203 / 48T LBS - shock resistant	72220348
200 / 70T for thin-walled material / corrugated sheets	72120070
Accessories	Reference
Guide rail set 1.400 mm incl. 2 quick release clamps and 2 adapters	608275ASET
Set of 2 adapters for guide rail 1.400 mm	608275A

Max. cutting capacities				
	90°	45° (bevel cut)		
Round	67 x 6	42 x 4		
Square	67 x 67 x 6	42 x 42 x 4		
Angle	67 x 6	42 x 4		
Plan	10	8		
Cutting depth	67	42		

Connector for guide rail